



# 4200 SLIDING DOOR

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 1.5 (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: 1.02"

Maximum acoustic insulation: Rw = 39 dB.

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 3

Water tightness (UNE-EN 12208:2000):

Class 7A

Wind resistance (UNE-EN 12210:2000):

Class C5

\*Reference test 47.24" x 47.24" 2 sashes

SECTIONS	Frame: 2.36", 2.56", 3.03" and 3.15" Three-rail: 4.17" and 4.96" Sash: 1.30" and 1.46"	EXTRUSION ALLOY 6063 T-5
PROFILE THICKNESS	Window 0.059"	POLYAMIDE STRIP LENGTH Polyamide 6.6 reinforced with 25% fiberglass : From 0.57" to 0.79"
MAXIMUM DIMENSIONS	Width (L) = 86.61" Height (H) = 102.36"	OPENING POSIBILITIES Sliding door 2, 3, 4 and 6 sashes Optionally three-rail Optionally galandage mono-rail and two-rail with 1, 2 and 4 sashes
MAXIMUM WEIGHT/SASH	100 Kg Square cut assembly 200 Kg Wrap around sash	

Please consult maximum dimensions according to types.

## FINISHES

Colour powder coating (RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

