



# 4600 PLUS LIFT & SLIDE

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0.65$  (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing

## GLAZING

Maximum glazing: 2.56"

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Wind resistance (UNE-EN 12210):

Class 4

Class C5

SECTIONS	Frame 7.09"
	3 rails 11.02"
	4 rails 14.96"
	Sash 3.15"

EXTRUSION ALLOY

6063 T-5

OPENING POSSIBILITIES

Sliding

1 rail (1 sash + 1 fixed light), 2, 3 & 4 rails

Possibility of 90° opening without mullion

MAXIMUM DIMENSIONS	Width (L) = 129.9"
	Height (H) = 129.9"

MAXIMUM WEIGHT	400 Kg
-------------------	--------

Please consult maximum dimensions according to types

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras  
Standard Class 15

Optionally Class 20 y 25

Optionally bicoloured

