



4900 SLIDING HI

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.2$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: 1.42"

Maximum acoustic insulation: $R_w = 40$ dB

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class 7A

Wind resistance (EN 12210):

Class C5

Reference test 48.43" × 97.64" / 2 sashes

SECTIONS	2.36", 2.76", 3.50", 4.72", 4.92", 5.12", 4.96", 5.71" 3 rails 7.91" 4 rails
PROFILE THICKNESS	Window 0.063"
MAXIMUM DIMENSIONS	Width (L) = 86.61" Height (H) = 118.11"
MAXIMUM WEIGHT/SASH	240 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
----------	---

EXTRUSION ALLOY
6063 T-5
POLYAMIDE STRIP LENGTH
1.34"
OPENING POSSIBILITIES
Sliding Possibility of 1, 2, 3 & 4 rails Possibility of galandage
AVIS TECHNIQUE CERTIFICATE
DTA certification from CSTB lab

