



# A 84 HIDDEN SASH - PVC

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 0.74 (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: 1.83"

Maximum acoustic insulation: Rw = 46 dB

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207):

Class 4

Water tightness (UNE-EN 12208):

Class E<sub>2250</sub>

Wind resistance (UNE-EN 12210):

Class C5

Reference test window 48.43" × 58.27 "2 sashes.

SECTIONS	Frame 3.31" Sash 3.31"		GASKETS	EPDM Triple GASKET	
CLASIFICACION	Profile thickness Class A ≥ 0.11" Weather Severe weather Impact Class II		OPENING POSIBILITIES	INWARDS	Side hung, turn&tilt, parallel tilt, tilt, bottom hung.
MAXIMUM DIMENSIONS	Width (L) = 17.72"-55.12" Height (H) = 17.72"-86.61"		FINISHES	Optionally bicoloured White Smooth colours Wood-imitation effect	
MAXIMUM WEIGHT/SASH	130 Kg Window	130 Kg Balcony			

Please consult maximum dimensions according to types.

