



A 84 HINGED - PVC

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U from 0.79(W/mK)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 2.13"

Maximum accoustic insulation: $R_w = 46$ dB

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1500

Wind resistance (EN 12210):

Class C5

Reference test window 48.43" × 58.27" 2 sashes.

SECTIONS	Frame 3.31" Sash 3.31"		GASKETS	
CLASIFICATION	Profile thickness Class A ≥ 0.11"		EPDM Triple GASKET	
	Weather Severe weather Impact Class II		OPENING POSSIBILITIES	
MAXIMUM DIMENSIONS	Width (L) = 17.72"-55.11" Height (H) = 17.72"-96.46" Window		INWARDS	Side hung, turn&tilt, parallel tilt, tilt.
	Width (L) = 17.72"-55.12" Height (H) = 23.62"-98.43" Balcony		OUTWARDS	Side hung (Door)
	Width (L) = 27.56"-51.18" Height (H) = 23.62"-98.43" Balcony		FINISHES	
MAXIMUM WEIGHT/SASH	130 Kg Window -Balcony	160 Kg Door	Optionally bicoloured White Smooth colours Wood-imitation effect	

Please consult maximum dimensions according to types.

