

BA-45

Thermal efficiency	
Uw*	6,1* W/m ² K
U factor*	1,08* Btu/h·ft ² ·F
*	Reference window with dimensions of 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BA 45
Installation depth	Frame: 2.12 in Sash: 1.77 in
Number of chambers	1
Thermal Break	None
Number of seals	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package	Float 0.15 in
Ug value	5,8 W/m ² K
Glazing package thickness	Glazing thickness available from 0.15 to 1.33 in
Sound insulation of available glazing	Rw: from 31 to 42 dB
Fittings	
Types	---
Hinges	Surface
Anti-theft protection	anti-theft catches
Microventilation	Yes
Other	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	62.9 in
Maximum window height – single sash	94.48 in
Maximum window width - double sash with a movable post	118.11 in
Maximum window height – double sash with a movable post	94.48 in
Maximum sash area	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in