

BA-77

Thermal efficiency	
Uw*	1,0 W/m ² K
U factor*	0,18 Btu/h·ft ² ·F
*	Glass 4/18/4/18/4 window size 48 7/16 in x 58 4/16 in (1230 mm x 1480 mm)
Profile	
Profile name	BA 77
Installation depth	Frame 3.031 in Sash 3.386 in
Number of chambers	4
Thermal Break	Yes: 1.693 in
Number of seals	2
Glass	
Glazing package	4/18/4/18/4 warm spacer bar
Ug value	0,5 W/m ² K
Glazing package thickness	from 0.8 to 2.638 in
Sound insulation of available glazing	---
Fittings	
Types	Winkhaus circumferential
Hinges	surface
Anti-theft protection	anti-theft catches
Microventilation	Yes
Other	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	66.9 in
Maximum window height – single sash	110.2 in
Maximum window width - double sash with a movable post	133.8 in
Maximum window height – double sash with a movable post	110.2 in
Maximum sash area	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in