

BA-65US

Thermal efficiency	
Uw*	1,3 W/m ² K
U factor*	0,23* Btu/h·ft ² ·F
*	Reference window with dimensions of 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BA-65US
Installation depth	Frame 2.55 in Sash 2.9 in
Number of chambers	3
Thermal Break	1.18 in thick glass-fibre reinforced polyamide
Number of seals	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package	4/18/4/18/4
Ug value	0,5 W/m ² K
Glazing package thickness	Glazing thickness available from 0.5 to 2.36 in
Sound insulation of available glazing	Rw: from 31 to 47 dB
Fittings	
Types	---
Hinges	surface
Anti-theft protection	anti-theft catches
Microventilation	Yes
Other	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	62.9 in
Maximum window height – single sash	94.48 in
Maximum window width - double sash with a movable post	125.98 in
Maximum window height – double sash with a movable post	94.48 in
Maximum sash area	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in