

BA-65USCL

Thermal efficiency	
Uw*	1,4 W/m ² K
U factor*	0,25* Btu/h·ft ² ·F
*	Reference window with dimensions of 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BA-65USCL
Installation depth	Frame 2.55 in Sash 2.9 in
Number of chambers	3
Thermal Break	1.18 in thick glass-fibre reinforced polyamide
Number of seals	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package	4/16/4
Ug value	1,0 W/m ² K
Glazing package thickness	Glazing thickness available: from 0.9 to 1.18 in
Sound insulation of available glazing	---
Fittings	
Types	---
Hinges	concealed
Anti-theft protection	Anti-theft catch for Tilt and Turn
Microventilation	Yes
Other	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	49.2 in
Maximum window height – single sash	86.6 in
Maximum window width - double sash with a movable post	118.1 in
Maximum window height – double sash with a movable post	86.6 in
Maximum sash area	3 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in