

## BAQ-82 AL

Thermal efficiency	
Uw*	0,77 W/m <sup>2</sup> K
U factor*	0,13* Btu/h·ft <sup>2</sup> ·F
*	Glass 4/18/4/18/4. gas: argon, warm edge spacer, window size 48 7/16in x 58 4/16in (1230mm x 1480mm)
Profile	
Profile name	BAQ-82AL
Installation depth	3.425 in
Number of chambers	7
Thermal Break	---
Number of seals	3
Glass	
Glazing package	4/18/4/18/4
Ug value	0,5 W/m <sup>2</sup> K
Glazing package thickness	1.89 in
Sound insulation of available glazing	---
Fittings	
Types	---
Hinges	surface
Anti-theft protection	2 Anti-theft catches
Microventilation	Yes
Other	---
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	59.05 in
Maximum window height – single sash	101.378 in
Maximum window width - double sash with a movable post	82.08 in
Maximum window height – double sash with a movable post	97.63 in
Maximum sash area	2,25 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m <sup>2</sup> and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in