

## BWC-92

Thermal efficiency	
Uw*	0,85 W/m <sup>2</sup> K
U factor*	0,12* Btu/h·ft <sup>2</sup> ·F
*	Glass: 4/12/4/12/4/12/4; gas: argon; warm edge spacer; window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BWC 92
Installation depth	3.6 in
Number of chambers	n/a
Thermal Break	n/a
Number of seals	3
Glass	
Glazing package	4/16/4/16/4
Ug value	0,5 W/m <sup>2</sup> K
Glazing package thickness	1.7 in
Sound insulation of available glazing	---
Fittings	
Types	---
Hinges	surface
Anti-theft protection	1 anti-theft catches RU
Microventilation	Yes
Other	handle rotation lock with a lifter
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	59 in
Maximum window height – single sash	100.3 in
Maximum window width - double sash with a movable post	81.9 in
Maximum window height – double sash with a movable post	100.3 in
Maximum sash area	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m <sup>2</sup> and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in