

## BWC-78 AL

Thermal efficiency	
Uw*	0,89 W/m <sup>2</sup> K
U factor*	0,16* Btu/h·ft <sup>2</sup> ·F
*	Glass: 4/14/4/14/4, gas: argon, warm edge spacer, window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name	BWC-78 AL
Installation depth	3.62 in
Number of chambers	n/a
Thermal Break	n/a
Number of seals	3
Glass	
Glazing package	4/14/4/14/4
Ug value	0,6 W/m <sup>2</sup> K
Glazing package thickness	1.575 in
Sound insulation of available glazing	---
Fittings	
Types	---
Hinges	surface
Anti-theft protection	1 anti-theft catch
Microventilation	Yes
Other	---
Handles	
Colors	---
Handle model	1006
Dimensions	
Maximum window width – single sash	59.05 in
Maximum window height – single sash	99.4 in
Maximum window width - double sash with a movable post	81.89 in
Maximum window height – double sash with a movable post	99.4 in
Maximum sash area	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m <sup>2</sup> and weight of 250 kg)	137.8 x 114.1 in lub 137.8 x 114.1 in