

BVQ-76

| Thermal efficiency | |
|--|--|
| Uw* | 0,80 W/m ² K |
| U factor* | 0,14* Btu/h·ft ² ·F |
| * | Glass: 4/14/4/14/4, gas: argon, warm edge spacer, window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm) |
| Profile | |
| Profile name | BVQ-76 |
| Installation depth | 2.9 in |
| Number of chambers | 6 |
| Thermal Break | None |
| Number of seals | 3 |
| Glass | |
| Glazing package | 4/16/4/18/4 |
| Ug value | 0,5 W/m ² K |
| Glazing package thickness | 1.8 in |
| Sound insulation of available glazing | --- |
| Fittings | |
| Types | --- |
| Hinges | Surface |
| Anti-theft protection | 2 Anti-theft catches |
| Microventilation | Yes |
| Other | --- |
| Handles | |
| Colors | --- |
| Handle model | 1006 |
| Dimensions | |
| Maximum window width – single sash | 59 in |
| Maximum window height – single sash | 97.4 in |
| Maximum window width - double sash with a movable post | 81.9 in |
| Maximum window height – double sash with a movable post | 94.5 in |
| Maximum sash area | 2,25 m ² |
| Maximum size of fixed glazing (when using a special glass, Maximum area of 7m ² and weight of 250 kg) | 137.8 x 114.1 in lub 137.8 x 114.1 in |