



# COR 2000

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 1.8 (W/mK)<sup>2</sup>

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: 1.18"

Maximum acoustic insulation: Rw = 39 dB.

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class 9A

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 47.24" × 46.46" 2 sashes.

SECTIONS	Frame 1.77" Sash 2.09"
PROFILE THICKNESS	Window 0.059" Door 0.067"
MAXIMUM DIMENSIONS	Width (L) = 59.06" Height (H) = 94.49"
MAXIMUM WEIGHT/SASH	120 Kg.

Please consult maximum dimensions according to types.

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25
----------	--

HERRAJE	Optionally concealed hinges Optionally security hardware
---------	---

EXTRUSION ALLOY
6063 T-5

GASKETS
EPDM triple gasket

OPENING POSIBILITIES	
INWARDS	Side hung, turn&tilt, bi-fold, tilt and parallel-tilt
OUTWARDS	Side hung, top hung and pivoting on horizontal or vertical axis

