



COR 3500

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 1.0 (W/mK)²

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 1.61"

Maximum acoustic insulation: Rw = 46 dB.

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1200

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 47.24" × 47.24" 2 sashes.

| | |
|---------------------|---|
| SECTIONS | Frame 2.13" Sash 2.48" |
| PROFILE THICKNESS | Window 0.059" Balcony 0.067" |
| MAXIMUM DIMENSIONS | Width (L) = 59.06" Height (H) = 94.49" |
| MAXIMUM WEIGHT/SASH | 120 Kg. |

Please consult maximum dimensions according to types.

| | |
|----------|---|
| FINISHES | Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured |
|----------|---|

| |
|-----------------|
| EXTRUSION ALLOY |
| 6063 T-5 |

| |
|--|
| POLYAMIDE STRIP LENGTH |
| Polyamide 6.6 reinforced with 25% fiberglass: 0.94" |

| |
|--------------------|
| GASKETS |
| EPDM triple gasket |

| |
|--|
| FOAMS |
| Perimeter polyolefin foam in glazing rebate zone |

| | |
|----------------------|--|
| OPENING POSIBILITIES | |
| INWARDS | Side hung, turn&tilt, bi-fold, tilt and paralel tilt |
| OUTWARDS | Side hung and top hung |

