



COR 60 HIDDEN SASH

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 1.5$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: 1.34"

Maximum acoustic insulation: $R_w = 45$ dBA

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class 9A

Wind resistance (EN 12210):

Class C5

Reference test 44.49" × 45.67" / Sash

SECTIONS	Frame 2.36" Sash 2.36"	EXTRUSION ALLOY	6063 T-5
PROFILE THICKNESS	Window 0.063" Balcony 0.063"	POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass : 0.94"
MAXIMUM DIMENSIONS	Width (L) = 51.18" Height (H) = 94.49"	GASKETS	EPDM triple gasket
MAXIMUM WEIGHT/SASH	160 Kg	OPENING POSIBILITIES	INWARDS Side hung, tilt and turn&tilt
FINISHES	Colour powder coating (RAL, mottled, rough...) According Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured		
HERRAJE	Optionally concealed hinges Optionally security hardware		

