



COR 80 INDUSTRIAL

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0.71$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: 2.87"

Maximum acoustic insulation: $R_w = 46$ dB

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1950

Wind resistance (EN 12210):

Class C5

Burglar resistance (EN 1627):

Grade RC2 (WK2)

Reference test 48.43" x 58.27" / 2 sashes

SECTIONS	Frame 3.15" Sash 3.46"
PROFILE THICKNESS	Window 0.059" Balcony 0.063"
MAXIMUM DIMENSIONS	Width (L) = 59.06" Height (H) = 102.36"
MAXIMUM WEIGHT/SASH	160 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewma Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
----------	---

EXTRUSION ALLOY
6063 T-5

POLYAMIDE STRIP LENGTH
Polyamide 6.6 reinforced with 25% fiberglass: 1.77"

GASKETS
EPDM triple gasket

FOAMS
Perimeter polyolefin foam in glazing rebate zone

OPENING POSSIBILITIES	
INWARD	Side hung, tilt & turn, parallel sliding and tilt
OUTWARD	Side hung and top hung projecting

CERTIFICATES	
SKG Certification	
Certification ATG - 3235	

