

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0.9$ (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 1.73"

Maximum acoustic insulation: $R_w = 45$ dB

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class E1200

Wind resistance (EN 12210):

CE 2400

Reference test 56.69" × 52.36" / 1 sash + 1 fixed light

Security test: **PAS24** ☒

Passed

Reference test 56.69" × 52.36" / 1 sash + 1 fixed light

SECTIONS	Frame 2.76" Sash 2.76"
PROFILE THICKNESS	Window 0.063"
MAXIMUM DIMENSIONS/ SASH	Slim sash / Side hung Width (L) = 37.40" Height (H) = 51.18"
	Slim sash / Top hung Width (L) = 47.24" Height (H) = 51.18"
	Heavy duty sash / Side hung Width (L) = 29.53" Height (H) = 68.90"
	Heavy duty sash / Top hung Width (L) = 70.87" Height (H) = 70.87"
MAXIMUM WEIGHT/SASH	Slim sash
	Side hung 35 Kg / Top hung 50 kg
	Heavy duty sash
	Side hung 42 Kg / Top hung 100 kg

Consult maximum weight and dimensions in accordance to typology.

OPENING POSSIBILITIES

OPEN OUT side hung and top hung

FINISHES

Colour powder coating

(RAL, mottled, rough...)

According Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

POLYAMIDE STRIP LENGTH

1.26"

