



EQUITY FACADE

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_{cw} \geq 0.6$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: 2.52"

Minimum glazing: 0.16"

SECTIONS	Mullion 0.71" Transom 0.71"
----------	--------------------------------

PROFILE THICKNESS	0.10" (Mullion and Transom)
-------------------	-----------------------------

Please consult maximum dimensions according to types

OPTIONS FOR COVERS Flat cover
3.35" deep elliptical cover H shape cover, 1.34" deep Rectangular cover: 0.55", 0.75", 3.94" & 5.71" deep Pyramid shape cover, 6.10" deep

EXTRUSION ALLOY
6063 T-6

THERMAL BREAK
0.24", 0.47" & 1.18" stackable thermal break profiles

GASKETS EPDM
Optionally Totally Vulcanized Corner Gasket

FINISHES

Colour powder coating (RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

