

MEDITERRANEAN BALCONY

ENERGY EFFICIENCY

Thermal Transmission Coefficient Uw from 2.1 (W/mK)²

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: 1.18"

Maximum accoustic insulation: Rw = 35 dB.

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000): Class 3
Water tightness (UNE-EN 12208:2000): Class 8A
Wind resistance (UNE-EN 12210:2000): Class C4

*Reference test 58.66" x 48.82" 1 Sash + 1 fijo

SECTIONS	Frame 4.17" Three-rail 6.34" Sash 1.77"
PROFILE THICKNESS	Balcony 0.059"
MAXIMUM DIMENSIONS	Width (L) =86.61" Height (H) = 102.36"
MAXIMUM	
WEIGHT/SASH	240 Kg
THICKNESS MAXIMUM DIMENSIONS MAXIMUM	Width (L) =86.61" Height (H) = 102.36"

Please consult maximum dimensions according to types.

EXTRUSION ALLOY

6063 T-5

OPENING POSIBILITIES

Sliding mono-rail:

- 1 Sash + 1 fix - 2 Sashes + 2 Fix

Two-rail sliding door 2, 3 and 4 sashes Optionally galandage 1 and 2 sashes

Optionally three-rail

FINISHES

Colour powder coating (RAL, mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25

