



MILLENNIUM PLUS 70 DOOR

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_w \geq 0,9$ (W/m²K)

Please consult typology, dimensions and glazing

ACCUSTIC INSULATION

Maximum glazing: 2.13"

Maximum accustic insulation: $R_w = 38$ dBA

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207):

Class 4

Water tightness (EN 12208):

Class 6A

Wind resistance (EN 12210):

Class C4

Reference test: window 47.24" x 90.56" 1 sash

Resistance to soft body impact (EN 13049)

Class 5 (max)

Reference test: Door 70.87" x 86.61" / 2 sashes. Laminated glass 3+3

Resistance to repeated opening and closing(EN 1191)

1.000.000 cycles

Test on door reference 36.81" x 82.68" / 1 sash.

SECTIONS	Frame 2.76" Sash 2.76"
PROFILE THICKNESS	Door 0.079"
MAXIMUM DIMENSIONS	Width (L) = 70.87" Height (H) = 0.118" Door Width (L) = 0.059" Height (H) = 0.118" Concealed-hinge-door
MAXIMUM WEIGHT/SASH	220 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured
----------	---

CERTIFICATES

SKG Certification



EXTRUSION ALLOY	
6063 T-5	
POLYAMIDE STRIP LENGTH	
Polyamide 6,6 reinforced with 25% fiberglass: 0.94"	
GASKETS EPDM	
Triple gasket	
FOAMS	
Perimeter polyolefin foam in glazing rebate zone.	
OPENING POSSIBILITIES	
INWARD	Side hung 1 or 2 sashes
OUTWARD	Side hung 1 or 2 sashes
AUTOMATIC	Inwards and outwards side hung 1 sash

