

ALCHEMY PEARL DECOR/33,3X100X0,98/R

Model: **ALCHEMY PEARL DECOR/33,3X100X0,98/R**

Reference: **40324** **PEARL**

Size: **33,3X100** cm

Thickness: **9,80** mm

Finish: **Natural**

Body Type: **WALL TILE - GROUP BIII**

GL - GLAZED Ceramic Tile

Water absorption

EN ISO-10545-3	Water absorption	> 10%
----------------	------------------	-------

Dimensional characteristics

EN ISO-10545-2	Surface quality	> 95%
EN ISO-10545-2	Curvature flatness	0,5/-0,3% +2,0/-1,5 mm
EN ISO-10545-2	Thickness	± 10% / ± 0,5 mm
EN ISO-10545-2	Length and Width	± 0,5 % / ± 2,0 mm
EN ISO-10545-2	Rectangularity	± 0,5% / ± 2,0 mm
EN ISO-10545-2	Straightness of sides	± 0,3 % / ± 1,5 mm

Mechanical characteristics

EN ISO 10545-11	Crazing resistance	Pass
EN ISO 10545-9	Thermal shock resistance	Pass
EN ISO-10545-4	Breaking strength	> 600 N
EN ISO-10545-4	Modulus of rupture	> 12 N/mm2

Surface characteristics

EN ISO 10545-7	Visible failure at No of revolutions	-
EN-101	Surface scratch resistance	3

Chemical characteristics

EN ISO-10545-13	High concentrations of acids and alkalis	HA/HA/HA
EN ISO-10545-13	Low concentrations of acids and alkalis	LA/LA/LA
EN ISO-10545-13	Household chemicals and swimming pool salts	A/A
EN ISO-10545-14	Stain resistance	5/-/5/5

ALCHEMY PEARL DECOR/33,3X100X0,98/R

Model: **ALCHEMY PEARL DECOR/33,3X100X0,98/R**

Reference: **40324** **PEARL**

Size: **33,3X100** cm

Thickness: **9,80** mm

Finish: **Natural**

Body Type: **WALL TILE - GROUP BIII**

GL - GLAZED Ceramic Tile

Non-slip characteristics

DIN-51130

Critical angle (footwear)

-

CE MARKING



CE Declaration of Performance: **004CPR2017-08-01**