



MILLENNIUM PIVOT DOOR

RPT

ENERGY EFFICIENCY

Thermal Transmission Coefficient

UD \geq 0.86 (W/mK)

Consult typology, dimensions and filling

ACCUSTIC INSULATION

Panel: 3.15"

Maximum glazing: 2.52"

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207)

Class 4

Water tightness (UNE-EN 12208)

Class 5A

Wind resistance (UNE-EN 12210)

Class C5

Reference test: window 47.24" \times 78.74" / 1 sash.

| | | |
|---------------------|---|------------------------|
| SECTIONS | Frame 3.15" Sash 3.15" | EXTRUSION ALLOY |
| | | 6063 T-5 |
| PROFILE THICKNESS | Door 0.079" | POLYAMIDE STRIP LENGTH |
| | | 0.94" / 1.02" |
| MAXIMUM DIMENSIONS | Width (L) = 82.68" (66.93" + 15.75") Height (H) = 118.11" <small>*Measured from pivot axis</small> | GASKETS |
| | | Double gasket |
| MAXIMUM WEIGHT/SASH | 250 Kg | OPENING POSIBILITIES |
| | | Pivoting |
| FINISHES | Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns Wood effect powder coating According to Qualideco Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured | |

