



# FACADE SST 52

TBB

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_{cw} \geq 0.8$  (W/m<sup>2</sup>K)

Please consult typology, dimensions and glazing

## GLAZING

Maximum glazing: 1.10"

Minimum glazing: 0.24"

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12152):

Water tightness (EN 12154):

Wind resistance (EN 13116):

Reference test 118.11" x 137.80"

Class AE

Class RE750

PASSED Design loading 1200 Pa-Security loading 1800 Pa

|                     |                                                                                                                               |                                             |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| SECTIONS INWARDS    | Mullion 2.05"<br>Transom 2.05"                                                                                                | EXTRUSION ALLOY                             |
| PROFILE THICKNESS   | Mullion 0.083" and 0.118"<br>Transom 0.083"                                                                                   | 6063 T-6                                    |
| MAXIMUM DIMENSIONS  | Hidden Top Hung<br>Width max. (L) = 98.43"<br>Height max. (H) = 98.43"<br>Width min. (L) = 19.69"<br>Height min. (H) = 25.59" | GASKETS                                     |
| MAXIMUM WEIGHT/SASH | 180 kg Top hung opening<br>350 Kg Fixed lights                                                                                | Optionally Totally Vulcanized Corner Gasket |
|                     |                                                                                                                               | THERMAL BREAK                               |
|                     |                                                                                                                               | 0.71"                                       |
|                     |                                                                                                                               | OPENING POSSIBILITIES                       |
|                     |                                                                                                                               | Outward: Hidden Top Hung                    |

Please consult maximum dimensions according to types

## FINISHES

Colour powder coating (RAL,  
mottled, rough...)

According to Qualicoat > 60 microns

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras  
Standard Class 15

Optionally Class 20 and 25  
Optionally bicoloured



Certification CWCT.  
British Standard

