



# SLIDING ROOF

## SLOPE

Profiles designed for 8.5° slope (15%).  
Slope up to 30° (57%) depending on fixing.

## GLAZING

- Celular polycarbonate 0.98"
- Sandwich panel 0.95".
- Glazing 0.95" (4 tempered/12/4+4)

## LIGHT

Maximum roof span: 189.0"  
Minimum roof span: 122.0"  
Span width: no limit (union of sets)

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

### Non-flooded roof water tightness

### COMPLIES

During the 6 h. of test duration, at the end of the trial and during the next 24 h, no dripping or humidity was detected under the cover. Reference test: Reference test: 169.3" x 163.8" with 3 movable rows, 9 sashes and glazing 4/12/4+4.

SECTIONS	Frame 5.24" Sash 1.10"
PROFILE THICKNESS	Sash 0.059"
MAXIMUM DIMENSIONS	Width (L) = 90.55" (polycarbonate and sandwich panel) 47.24" (glazing) Height (H) = 62.99"
MAXIMUM WEIGHT/SASH	75 Kg

Please consult maximum dimensions according to types.

OPENING POSIBILITIES	
SLIDING	Motorized sash opening Set of 2 sashes and 1 fix Maximum opening 66%
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Posibility Class 20 and 25

