



FACADE TP 52

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

$U_{cw} \geq 0.6$ (W/m²K)

Please consult typology, dimensions and glazing

GLAZING

Maximum glazing: 2.52"

Minimum glazing: 0.16"

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12152):

Water tightness (EN 12154):

Wind resistance (EN 13116):

Reference test 118.11" x 137.80"

Class AE

Class RE1350

PASSED Design loading 2000 Pa-Security loading 3000 Pa

PROFILE THICKNESS	Mullion 0.083" and 0.118" Transom 0.083"	EXTRUSION ALLOY	6063 T-6
WINDOW MAXIMUM DIMENSIONS	Hidden Top Hung Width max. (L) = 98.43" Height max. (H) = 98.43" Width min. (L) = 19.69" Height min. (H) = 25.59" Hidden Parallel Projecting Width max. (L) = 59.06" Height max. (H) = 118.11" Width min. (L) = 17.72" Height min. (H) = 20.87" Hidden Side Hung or Turn&Tilt Width max. (L) = 55.12" Height max. (H) = 74.80" Width min. (L) = 19.69" Height min. (H) = 23.62"	THERMAL BREAK	0.24", 0.47" and 1.18" stackable profiles
		GASKETS EPDM	Optionally Totally Vulcanized Corner Gasket
		OPTIONS FOR COVERS	3.35" deep elliptical cover H shape cover, 1.34" deep Rectangular cover: 0.55", 0.75", 3.94" & 5.71" deep Flat cover Pyramid shape cover, 6.10" deep
		OPENING POSSIBILITIES	Outward: Hidden top hung Hidden parallel projecting Inward: Hidden side hung / tilt & turn
MAXIMUM WEIGHT	200 kg Parallel projecting opening 180 kg Hidden top hung opening 100 Kg Tilt & turn opening 750 Kg Fixed glazing		

Please consult maximum dimensions according to types

FINISHES

Colour powder coating (RAL, mottled, rough...)

According to Qualicoat Standard > 60 microns

Wood effect powder coating

According to Qualideco Standard

Anodized

According to Ewwa Euras Standard

Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured



Certification CWCT.

British Standard

