



COR URBAN C16

TBB

ENERGY EFFICIENCY

Thermal Transmission Coefficient

Uw from 1.2 (W/mK)²

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: Outwards sash 0.87" / Inwards sash: **1.18"**

Maximum acoustic insulation: Rw = 50 dB.

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1650

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 48.43" × 58.27" 2 sashes

SECTIONS	Frame 4.80" Sash 4.76"	EXTRUSION ALLOY
PROFILE THICKNESS	Window 0.063"	6063 T-5
MAXIMUM DIMENSIONS	Width (L) = 47.24" Height (H) = 86.61"	POLYAMIDE STRIP LENGTH
MAXIMUM WEIGHT/SASH	150 Kg.	Polyamide 6.6 reinforced with 25% fiberglass : Frame 1.38" Sash 0.79"
FINISHES	Colour powder coating (RAL, mottled, rough...) According to Qualicoat > 60 microns Wood effect powder coating According to Qualideco standard Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured	GASKETS
		EPDM quadruple gasket
		OPENING POSIBILITIES
		INWARDS Side hung, turn&tilt. 1 and 2 sashes.

